DEVICE FOR CONTROLLING A TELECOMMUNICATIONS SYSTEM

FIELD OF THE INVENTION

The present invention relates to a device for controlling a telecommunications system made up of a plurality of networks, the networks being designed for services or parts of services, a network management device being
5   assigned to each network, and the network management devices being controllable by service management devices.

BACKGROUND INFORMATION

In the broadest sense, telecommunications systems are
10   made up of a plurality of networks, several of which are interconnected, depending on the particular requirement, to establish an end-to-end connection. To control and monitor such systems, a functional management architecture is required, as described, for example, in
15   ITU-T recommendations, in particular M.3010. A management architecture of this kind is schematically illustrated in Figure 2.

The lowest layer contains network elements NE, which are
20   each managed by an element management device EMS. Above that, resides a layer made up of network management devices NMS, to which service management devices SMS are linked at a higher level. The functions of service management device SMS can be assumed, in part, by the
25   customers themselves. This function is referred to as customer network management CNM. To manage the entire communications system in terms of business operations, the business management device BMS is then used.

30   In a nutshell, the network management devices are

SUBSTITUTE SPECIFICATION

responsible for monitoring and controlling the network elements situated in one geographic region, while the contractual aspects of the services provided to the customers are the focus of the service management device.

5 These include, inter alia, service orders, service complaints, and billing/accounting. In this connection, the concepts "NMF = network management function" and "SMF = service management function" were introduced for the functionalities allocated to the respective management

10 layers.

A capability of the communications system is to make available so-called end-to-end connections, a plurality of networks being required depending on the type of

15 connection. To provide this as a most versatile possible service, the service management devices must, therefore, access a multiplicity of network management devices NMS. The result in the available systems is, therefore, a so-called many-to-many relation, as illustrated in Figure

20 3. In the process, the number of interfaces required between the network management devices NMS and the service management devices SMS quickly becomes virtually unmanageable.

25 SUMMARY OF THE INVENTION
The present invention provides a device and method for controlling a telecommunications system made up of a plurality of networks, which will enable the service management devices to access the network management

30 devices required for the particular services.

The present invention further provides domain management devices, which enable the service management devices to access network management devices. The domain management

35 devices, in turn, have access to selected network management devices and are each able to be linked to a

SUBSTITUTE SPECIFICATION

service management device.

The present invention further provides a device which requires a substantially smaller number of interfaces at the service management devices and the network management devices than available devices.

The present invention further provides for a controllable matrix for linking the service management devices to the domain management devices. The present invention further provides for the controllable matrix to be controlled in conformance with the end-to-end connections to be managed in each instance.

The present invention further provides for at least one customer network management device to be connectable via the matrix. This renders possible a dynamic allocation between the particular network management devices and customer network management devices, without entailing additional outlay for switching equipment.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a block diagram of an exemplary embodiment according to the present invention.

Figure 2 shows a schematic representation of an available multilayer concept in accordance with the ITU-T recommendation.

Figure 3 shows an exemplary schematic representation of the many-to-many relations between service management devices and network management devices according to the present invention.

Figure 4 shows a block diagram of a further exemplary embodiment according to the present invention.

SUBSTITUTE SPECIFICATION

Figure 5 shows a block diagram of a domain management device employed in the device according to the exemplary embodiment of Figure 4 according to the present invention.

Figure 6 shows an exemplary end-to-end connection traversing a plurality of networks which are managed by a device according to the present invention.

Figure 7 shows a table illustrating certain improvements effected according to the present invention.

Figure 8 shows a table illustrating certain improvements effected according to the present invention.

Figure 9 shows a table illustrating certain improvements effected according to the present invention.

DETAILED DESCRIPTION

According to the present invention, Figure 1 illustrates three service management devices SMS, each of which is connected to three domain managers DM, to which three or two network management devices are connected, in turn. A comparison to Figure 3 reveals that substantially fewer interfaces are needed than is the case when working with an available device.

According to the present invention, Figure 3 illustrates five service management devices 1 through 5 able to be connected via a matrix 6, in the following, also referred to as a correlation matrix, to five domain managers 7 through 11. Domain managers 7 through 11 have access to network management devices, of which three network management devices 12, 13, 14, are shown as examples in Figure 4.

Also connected to correlation matrix 6 is a server 15 for
the customer network management. Moreover, correlation
matrix 6 is connected to two databases 16, 17, one being
used as database KD DB (customer database), and the other

5   as database SLA (= service level agreement). Server 15
can exchange data via two layers 18, 19 with customer
devices 20, layer 18 providing a suitable operational
structure in the sense of a corporate identity,
identifying the telecommunications carrier, while layer

10   19 is designed as a security layer. In addition, each of
network management devices 12, 13, 14 has assigned B-CNM
(= basic customer network management) devices, whose data
are fed to server 15.

15   Figure 5 depicts the functional units of a domain manager
7 through 11 (Figure 4). In this context, a management
information distributor 31 is employed for the connection
to correlation matrix 6 (Figure 4). A further data
processing device 32 is used for data preparation, for

20   precorrelation, and for converting from NMF to SMF.
Subsystem adapters 33, 34, 35, of which three are shown
illustratively in Figure 5, are used for the connection
to the particular network management devices.

25   In parallel to service management devices 1 through 5,
the service-oriented information is supplied to customer
network management server 15. This ensures a uniform,
comprehensive method for accessing the CNM information.
The customer databases, domain-, service-, and

30   customer-network management devices are linked with the
aid of correlation matrix 6, employing an object-based
communications infrastructure, which supports an
end-to-end service correlation and renders possible a
flexible modeling of complex services by combining the

35   information communicated by the domain managers.

SUBSTITUTE SPECIFICATION

This communications infrastructure enables the service-relevant interconnection objects of various domain managers to be queried by the responsible service management device SMS, and for status modifications to be

5   routed by the domain managers in dedicated fashion to service management device SMS. In addition, it provides the basis for transmitting customer queries from the customer network management system to service management device SMS and vice versa, to make available information

10   of relevance to the customer, from service management device SMS via the customer network management system. Also the basic information for the correlation is fed via this communications infrastructure to the domain managers, service management devices SMS, and to the

15   customer network management systems.

The functionality of the domain managers resides in the adaptation of the subsystems, in the conversion of the network management information received from the

20   subsystems, from the domains of fault, performance, and configuration management, into service-oriented information, as well as in the conversion of requests received from the service management devices into network management requests, and in the routing of such requests

25   to the appropriate network management devices. The interface directed to service management devices is designed as a standardized, object-oriented interface, and is integrated in the communications infrastructure. Moreover, the domain manager assures the bidirectional

30   exchange of information, and that the requests contained in the security concept with respect to access restrictions to the network management devices and with respect to the integrity and confidentiality of the data are observed (security management functions).

35

Figure 6 depicts the networks and management devices used

SUBSTITUTE SPECIFICATION

for a frame-relay end-to-end connection. The connection is established between two terminal devices 41, 42, shown as computers, in each case via a customer service switch 43, 44, access networks 45, 46, and an ATM network 47 as

5   a backbone network. A network management device 48, 49, 50 is provided to manage each of these networks. Each of these network management devices is assigned, together with other network management devices, to a domain manager 51, 52. A service management device 53 has access

10   to domain managers 51, 52 via a correlation matrix that is not shown in Figure 6. For purposes of exchanging data, customer database 16 is linked to the domain managers and to service management device 53. Moreover, customer network management device 54 is connected to the

15   service management device. The end-to-end connection from point A to point B is displayed on a screen 55 of customer network management device 54, making it possible for an operator to visualize the status of the connection and to intervene in case of errors.

20

Some of the benefits of the device according to the present invention are elucidated in the following on the basis of an application example, where service and customer network management are made available for

25   services based on ATM, frame relay, and leased link. For this, network management information from the following networks is to be integrated:
- 3 NMS for access components (B-NT-NMS, DTNMS and router NMS);

30   - 2 NMS for leased link (BFS, 46020);
- 3 NMS for ATM (Nortel NMS, 46020, NavisCore);
- 1 NMS for frame relay (Nortel NMS).

The relevance of the management information from the

35   management perspective can be inferred from Figure 7.

From this it is apparent that, on the average, two
interfaces are required per network management device in
the direction of the service management devices; and five
to seven interfaces per service management device in the
5   direction of the network management devices.

Figure 8 depicts the interfaces required at the domain
managers in the direction of the individual networks and
vice versa; while Figure 9 illustrates the interfaces
10   required between the domain managers and the service
management devices. One can discern that, regardless of
the number of service management devices and
independently of the service modeling, only one interface
is needed for each network management device. The
15   advantages are particularly evident by the reduction in
the load on the network management devices and the
networks resulting from the transfer of management
information. Also, the number of subnetwork management
devices to be integrated per domain is substantially less
20   than the number needed for a direct integration.

The correlation matrix can be used to properly channel
the information relevant to the individual service
management devices by performing a one-time correlation
25   to administrative customer data. Customer network
management server 15 can be interfaced in such a way that
all information relevant to customer network management
is acquired via the correlation matrix as
service-spanning information, but is provided with
30   customer and service identification.